


PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65D 19/42 // B62B 3/00	A1	(11) International Publication Number: WO 00/51898 (43) International Publication Date: 8 September 2000 (08.09.00)
(21) International Application Number: PCT/SE00/00361 (22) International Filing Date: 24 February 2000 (24.02.00) (30) Priority Data: 9900717-1 1 March 1999 (01.03.99) SE (71) Applicant (for all designated States except US): ARCA SYSTEMS AB [SE/SE]; S-284 80 Perstorp (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): BROADLEY, Mike [GB/GB]; Beechwood House 2 Fountain Lane, Davenham, Cheshire CW9 8LX (GB). (74) Agent: STENBERG, Yngve; Perstorp AB, S-284 80 Perstorp (SE).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: TRANSPORTATION MEANS**(57) Abstract**

Transportation means (1) comprising a pallet-like carrying structure (2) with long sides (21), short sides (22), four corners (23), an upper surface (24) and a lower surface (25). The carrying structure is provided with wheels (3) at each of the four corners (23). The upper surface (24) is furthermore provided with receiving means which are intended to receive the wheels (3) of a second transportation means (1) stacked on top of a first transportation means (1) so that a number of such transportation means may be stacked thereon. The upper surface (24) is provided with two narrow long side channels (25) arranged parallel to the long sides (21) and stretching from one short side (22) to the other, the long side channels (25) being placed at a distance from each other which is mainly equal to the distance between the wheels (3), as seen from a short side (22). A transportation means (1) may hereby be placed on top of each other by rolling them into engagement with each other in a lengthways direction.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Transportation means

The present invention relates to a transportation means comprising a pallet-like carrying structure provided with wheels.

Transportation means consisting of a carrying structure provided with wheels on the lower side has been known for a long time. They are most often of a format adapted to containers used for transportation and storage of goods. Most common formats, as seen from above, are 0.4 x 0.6 metres and 0.6 x 0.8 metres. The transportation means do, of course, need to be transported empty from time to time. In order to do that, the transportation means need to be stacked on top of each other. Since they are provided with wheels they will roll around and a stack will be impossible to handle. There are a number of ways to secure such a stack.

One known such way is to alternately turn the transportation means 90° so that they rest, not on their wheels, but on the carrying structure itself. In order to secure the stack, the carrying structure is provided with guiding means on the rim. This solution is known from GB 2 207 894. The disadvantage with this solution is that the stack will not be adapted to any pallet format standard. Such a stack will therefore be a bit bulky.

Another way to solve the problem is shown in GB 0 904 198 where the upper surface of the carrying structure is provided with small pockets which is intended to accommodate the wheels. The problems with this solution is that it is a bit difficult to position the transportation means exactly enough to make the wheels engage the pockets.

A slight improvement upon GB 0 904 198 is known from EP 0 675 829. The upper surface has here been provided with a bowl-like structure with a shape that corresponds to the radius of the swivel castor wheel as rotated around the swivelling axis. It will be a bit easier to position a transportation means according to EP 0 675 829 when compared to GB 0 904 198 but the design will allow some sideways movement which does not provide a perfect vertical alignment of the stack.

A variation of EP 0 675 829 which also gives some improvement upon the same is known from GB 2 281 897 where the bowl-like shapes known from EP 0 675 829 have been provided with sloping partition walls guiding the wheels into four narrow pockets. The disadvantage with this solution is that swivel castor wheels might be stuck on top of the partition wall. You will furthermore have to position the transportation means rather exactly in order to make it fall into the correct position.

All of the above transportation means suffer from the disadvantage that they have to be positioned onto one another by being lowered from above in a more or less vertically aligned position when being stacked. This works rather well, although it is

time consuming, as long as the stack is relatively low. It will however be rather difficult to position the transportation means when the stack reaches shoulder height and above. This is specially pronounced when they are heavy. There is also an ergonomical aspect to the stacking since the transportation means will have to be lifted into engagement. Neck, back and shoulder problems are most likely to occur if this stacking operation is repeated for a longer period of time.

According to the present invention a transportation means which is much easier to handle has been achieved. The invention relates to a transportation means comprising a pallet-like carrying structure with two long sides, two short sides, four corners, an upper surface and a lower surface. The carrying structure is provided with wheels at each of the four corners. At least two of the wheels are possibly of the swivel castor wheel type. The upper surface is furthermore provided with receiving means which are intended to receive the wheels of a second transportation means stacked on top of a first transportation means so that a number of such transportation means may be stacked, and fixated horizontally, on top of each other. The invention is characterised in that the upper surface is provided with two narrow long side channels arranged parallel to the long sides and stretching from one short side to the other. The long side channels are placed at a distance from each other which is mainly equal to the distance between the wheels, as seen from a short side. The transportation means may be placed on top of each other by rolling them into engagement with each other in a lengthways direction.

The upper surface is preferably provided with a rim used for locating and horizontally fixate goods, placed on top of the upper surface. Each short side end of the long side channels is furthermore provided with a channel stopper, which channel stopper is connected to the rim or being a part of the rim.

The long side channels are preferably provided with inner channel stoppers placed at a distance from each of the short side ends of the long side channels, which distance is adapted to the radius of the wheels. A wheel is hereby prevented from moving inwards in the long side channel. The inner channel stoppers are suitably placed at a position corresponding to the vertical swivelling axis of the swivel castor wheels.

According to one embodiment of the invention the upper surface is provided with a pair of secondary channels placed parallel to the short sides and crossing the long side channels. The longitudinal centreline of each of the secondary channels is preferably coinciding with the centreline of the inner channel stopper and thereby also the swivelling axis of the swivel castor wheels.

It will hereby be possible to roll a transportation means provided with four swivel castor wheels into engagement from any of the long sides or short sides.

Each short side end of the secondary channels is preferably provided with a secondary channel stopper, which secondary channel stopper is connected to the rim or being a part of the rim.

The carrying structure can be made of many different materials. Thermoplastic materials are, however, the ones most suited for the purpose. Among the most suited thermoplastic materials can be mentioned polyethylene, polypropylene, poly amide, polystyrene and acryl-butadiene-styrene. It is also possible to add reinforcing fibres to the material. Among processes possible for the manufacturing of a carrying structure of a transportation means according to the invention can be mentioned injection moulding, blow moulding, rotation moulding and twin sheet moulding.

The invention is explained further together with enclosed drawings, showing different embodiments of the invention wherein,

-figure 1 shows, in perspective a first embodiment of a transport means 1 according to the invention.

-figure 2 shows, in perspective a second embodiment of a transport means 1 according to the invention.

Figure 1 shows a transportation means 1 comprising a pallet-like carrying structure 2 with two long sides 21, two short sides 22, four corners 23, an upper surface 24 and a lower surface 25. The carrying structure is provided with wheels 3 at each of the four corners 23 of which two of the wheels 3 are of the swivel castor wheel type 3'. The upper surface 24 is furthermore provided with receiving means which are intended to receive the wheels 3 of a second transportation means 1 stacked on top of a first transportation means 1 so that a number of such transportation means may be stacked, and fixated horizontally, on top of each other. The upper surface 24 is provided with two narrow long side channels 25 arranged parallel to the long sides 21 and stretching from one short side 22 to the other. The long side channels 25 are placed at a distance from each other which is mainly equal to the distance between the wheels 3, as seen from a short side 22. Transportation means 1 may hereby be placed on top of each other by rolling them into engagement with each other in a lengthways direction. The upper surface 24 is provided with a rim 26 used for locating and horizontally fixate goods, placed on top of the upper surface 24. Each short side end of the long side channels 25 is provided with a channel stopper 25'. This channel stopper 25' is a part of the rim 26. The long side channels 25 are

provided with inner channel stoppers 25" placed at a distance from each of the short side ends of the long side channels 25, which distance is adapted to the radius of the wheels 3 so that the wheels 3 are prevented from moving inwards in the long side channel 25. The inner channel stoppers 25" are placed at a position corresponding to the vertical swivelling axis of the swivel castor wheels 3'.



Figure 2 shows a second embodiment of a transportation means 1 according to the invention. The embodiment shown in figure 2 corresponds in the main with the one shown in figure 1. The upper surface is, however, further provided with a pair of secondary channels 27 placed parallel to the short sides and crossing the long side channels 25. The longitudinal centreline of each of the secondary channels 27 is coinciding with the centreline of the inner channel stopper 25" and thereby also the swivelling axis of the swivel castor wheels 3'. Each short side end of the secondary channels 27 is provided with a secondary channel stopper 27', which secondary channel stopper 25' is a part of the rim 26.

The invention is not limited to the embodiments shown, since it can be varied in different ways within the scope of the invention. It is for example possible to provide a transportation means 1 according to the invention with four swivel castor wheels 3'. It will then be possible to roll such a transportation means 1 with an upper surface 24 as shown in figure 2 into engagement from any the two short sides 21 or long sides 22.

CLAIMS

1. Transportation means (1) comprising a pallet-like carrying structure (2) with two long sides (21), two short sides (22), four corners (23), an upper surface (24) and a lower surface (25), that the carrying structure is provided with wheels (3) at each of the four corners (23) of which at least two of the wheels (3) possibly are of the swivel castor wheel type (3'), that the upper surface (24) furthermore is provided with receiving means which are intended to receive the wheels (3) of a second transportation means (1) stacked on top of a first transportation means (1) so that a number of such transportation means may be stacked, and fixated horizontally, on top of each other, c h a r a c t e r i z e d in that the upper surface (24) is provided with two narrow long side channels (25) arranged parallel to the long sides (21) and stretching from one short side (22) to the other, the long side channels (25) being placed at a distance from each other which is mainly equal to the distance between the wheels (3), as seen from a short side (22), wherein transportation means (1) may be placed on top of each other by rolling them into engagement with each other in a lengthways direction.
2. Transportation means (1) according to claim 1, c h a r a c t e r i z e d in that the upper surface (24) is provided with a rim (26) used for locating and horizontally fixate goods, placed on top of the upper surface (24), and that each short side end of the long side channels (25) is provided with a channel stopper (25'), which channel stopper (25') is connected to the rim (26) or being a part of the rim (26).
3. Transportation means (1) according to claim 1 or 2 c h a r a c t e r i z e d in that the long side channels (25) are provided with inner channel stoppers (25'') placed at a distance from each of the short side ends of the long side channels (25), which distance is adapted to the radius of the wheels (3) so that a wheel (3) is prevented from moving inwards in the long side channel (25).
4. Transportation means (1) according to claim 3 c h a r a c t e r i z e d in that the inner channel stoppers (25'') are placed at a position corresponding to the vertical swivelling axis of the swivel castor wheels (3').
5. Transportation means (1) according to claim 3 or 4 c h a r a c t e r i z e d in that the upper surface is provided with a pair of secondary channels (27) placed parallel to the short sides and crossing the long side channels (25), that the longitudinal centreline of each of the secondary channels (27) is coinciding with the centreline of the inner channel stopper (25'') and thereby also the swivelling axis of the swivel castor wheels (3').

6. Transportation means (1) according to claim 5, characterized in that the each short side end of the secondary channels (27) is provided with a secondary channel stopper (27'), which secondary channel stopper (25') is connected to the rim (26) or being a part of the rim (26).

Fig. 1Fig. 2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00361

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B65D 19/42 // B62B 3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B65D, B62B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 3618422 A1 (CORDES, WERNER), 3 December 1987 (03.12.87) --	1-6
A	GB 2280166 A (LIN PAC MOULDINGS LIMITED), 25 January 1995 (25.01.95) --	1-6
A	GB 1583763 A (GPG INTERNATIONAL LIMITED), 4 February 1981 (04.02.81) --	1-6
A	GB 904198 A (REGINALD ROBERT HALL), 22 August 1962 (22.08.62) --	1-6

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 June 2000

Date of mailing of the international search report

05-07-2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Inger Löfgren/Els

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00361

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9842585 A1 (R.D. IMPEX A/S), 1 October 1998 (01.10.98) --	1-6
A	GB 2281897 A (LIN PAC MOULDINGS LIMITED), 22 March 1995 (22.03.95) -- -----	1-6

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/SE 00/00361

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	3618422	A1	03/12/87	NONE	
GB	2280166	A	25/01/95	NONE	
GB	1583763	A	04/02/81	NONE	
GB	904198	A	22/08/62	NONE	
WO	9842585	A1	01/10/98	AU 6392798 A	20/10/98
GB	2281897	A	22/03/95	NONE	